



Raven 1 60" x 32" x 20"
Raven 2 66" x 34" x 20"
Raven 3 72" x 36" x 20"

Acrylic Alcove Bath

Features

- Integral tile flange
- Sloped lumbar support
- Dual armrests
- Above floor rough-in
- Fits a standard 60", 66", 72" opening
- Available in both left and right end drain

Raven Series

Acrylic Alcove Bath

Raven 1 • RV 6032 L/R • 60" x 32" x 20" • 1524 mm x 813 mm x 508 mm

Raven 2 • RV 6634 L/R • 66" x 34" x 20" • 1676 mm x 864 mm x 508 mm

Raven 3 • RV 7236 L/R • 72" x 36" x 20" • 1829 mm x 914 mm x 508 mm

Tub Features

- Vacuum formed acrylic reinforced with fiberglass
- Scratch, stain and fade resistant high gloss finish

Whirlpool System

- ¾ HP pre-wired self draining pump and motor factory installed on a platform base
- 6 multi-directional adjustable flow whirlpool jets, 2 foot jets
- 4 spinner back jets included in all RVA L/RBW models
- Standard colour coordinated jets; polished chrome or brushed nickel also available as an upgrade
- Mounted air switch (A/S)

Jet Air System

- 8.5 Amp variable speed blower on a platform base
- 14 air jets Raven 1, 16 air jets Raven 2, 20 air jets Raven 3
- 4 air back jets included in model JRV 6032 JRV 6634, JRV 7236, L/R DB
- Standard colour coordinated jets; polished chrome or brushed nickel also available as an upgrade
- Mounted electronic touch control pad with on/off, speed, and oscillation control (E/C)

Ultimate Combo

- Includes all the whirlpool + jet air features with 6 whirlpool jets and 12 air jets, 4 spinner back jets, 2 foot jets Raven 1, 14 air jets Raven 2, 18 air jets Raven 3
- Standard colour coordinated jets; polished chrome or brushed nickel also available as an upgrade
- Mounted electronic touch control pad with on/off, (air and whirlpool), speed and oscillation control (E/C)

Optional Accessory


- Factory installed whirlpool heater

Meets or Exceeds the Following Specifications:

- CAN/CSA B45 Series
- CAN/ULC - S102.2 - M88 Flame Spread FRP laminate rating
- CAN/SCA - C22.2 No.218.2 - Hydromassage Standard

RV 6032 L/R • Bathtub

- RVA 6032 L/RAW • Whirlpool
- RVA 6032 L/RBW • Whirlpool with Backjet
- JRV 6032 L/RD • Jet Air
- JRV 6032 L/RDB • Jet Air with Backjet
- JV6032 L/RW • Combination



General Specifications


Average tub weight	62 lbs	28 kg
Average whirlpool weight	97 lbs	44 kg
Average jet air weight	75 lbs	34 kg
Average combination weight	101 lbs	46 kg
Bathing well dimensions at bottom	21 ½" x 45 ½"	546 mm x 1156 mm
Capacity to drain overflow	48 gallons	218 litres
Minimum operating space	36 gallons	164 litres
Bathtub water depth from drain to overflow	13"	330 mm
Drain opening diameter	2"	51 mm
Overflow opening diameter	2 ½"	64 mm
Drain to floor clearance	3"	76 mm

Electrical Specifications

Whirlpool Pump/Motor	¾ HP	7.5 AMP	120V
Jet Air Blower		8.5 AMP	120V

RV 6634 L/R • Bathtub

- RVA 6634 L/RAW • Whirlpool
- RVA 6634 L/RBW • Whirlpool with Backjet
- JRV 6634 L/RD • Jet Air
- JRV 6634 L/RDB • Jet Air with Backjet
- JV 6634 L/RW • Combination



General Specifications


Average tub weight	68 lbs	31 kg
Average whirlpool weight	103 lbs	47 kg
Average jet air weight	77 lbs	35 kg
Average combination weight	108 lbs	49 kg
Bathing well dimensions at bottom	23" x 50"	584 mm x 1270 mm
Capacity to drain overflow	52 gallons	236 litres
Minimum operating space	34 gallons	155 litres
Bathtub water depth from drain to overflow	12 ¾"	324 mm
Drain opening diameter	2"	51 mm
Overflow opening diameter	2 ½"	64 mm
Drain to floor clearance	3"	76 mm

Electrical Specifications

Whirlpool Pump/Motor	¾ HP	7.5 AMP	120V
Jet Air Blower		8.5 AMP	120V

RV 7236 L/R • Bathtub

- RVA 7236 L/RAW • Whirlpool
- RVA 7236 L/RBW • Whirlpool with Backjet
- JRV 7236 L/RD • Jet Air
- JRV 7236 L/RDB • Jet Air with Backjet
- JV 7236 L/RW • Combination



General Specifications

Average tub weight	73 lbs	33 kg
Average whirlpool weight	108 lbs	49 kg
Average jet air weight	81 lbs	37 kg
Average combination weight	112 lbs	51 kg
Bathing well dimensions at bottom	24" x 53"	610 mm x 1346 mm
Capacity to drain overflow	64 gallons	291 litres
Minimum operating space	45 gallons	204 litres
Bathtub water depth from drain to overflow	13"	330 mm
Drain opening diameter	2"	51 mm
Overflow opening diameter	2 ½"	64 mm
Drain to floor clearance	3"	76 mm

Electrical Specifications

Whirlpool Pump/Motor	¾ HP	7.5 AMP	120V
Jet Air Blower		8.5 AMP	120V

NOTES:

Bathtub to be installed on the floor supported by the 6 feet shim if required to level the bathtub for adequate drainage whirlpool and blower motor protrude outside the confines of the bathtub periphery for combination only.

Mirolin Industries Corp

60 Shorncliffe Road, Toronto, ON M8Z 5K1
 mirolin.com support@mirolin.com
 T 416 231 5790 800 MIROLIN (647 6546)
 F 416 231 0929 800 463 2236

Important:

Dimensions of fixtures are nominal and may vary ± 6 mm (¼"). These measurements are subject to change at Manufacturer's discretion.

